

### Facestock

A matt transparent polyester with ink and toner receptive topcoat.

Basis Weight	59 g/m <sup>2</sup>	ISO 536
Caliper	55 µm	ISO 534

### Adhesive

S4700 is a clear emulsion adhesive for demanding labelling applications.

### Liner

Hygroflat 100 FSC, a one side coated, bleached kraft paper.

The liner is made from FSC® certified paper (FSC Mix Credit, chain-of-custody number: CU-COC-807907, Licence Code: FSC-C004451).

Basis Weight	98 g/m <sup>2</sup>	ISO 536
Caliper	103 µm	ISO 534

### Laminate

Total Caliper	179 µm±10%	ISO 534
---------------	------------	---------

### Performance Data

Initial Tack	15 N/25mm	FTM 9 Glass
Peel Adhesion 90°	8 N/25mm	FTM 2 St.St.
Min. Application Temp.	0 °C	
Service Temperature	-20 °C to 80 °C	

### Adhesive Performance

S4700 is a clear permanent adhesive featuring excellent initial tack, adhesion and “wet-out” performance even on rough apolar surfaces such as HDPE. Improved temperature water, solvent and chemical resistance.

### Applications and Use

The product is primarily aimed at inventory and address labels for office use.

The hygroflat backing paper is specially suited to the more critical refolding demands of high-speed computer printers, providing optimum layflatness and excellent interfolding characteristics.

### Conversion and Printing

The inkjet matt transparent polyester is specially designed for sheet fed inkjet printing, providing optimal flatness during conversion, storage and the inkjet printing processing. Being relatively rigid, the film will not conform well to non-uniform or complex shaped surfaces. It is recommended that, when applicable, pre-printing by the roll label converter is via a low ink transfer method such as flexo. While it is possible to print via other conventional technologies it is recommended to test these first in case they effect the sensitive film surface.

### Compliance and Approvals

The adhesive S4700 is suitable for contact with dry, moist and fatty foodstuffs with a reduction factor of 4 or higher in this construction. For complete information regarding the food contact compliance status, please contact your local sales representative for a Food Contact Statement.

## AA401

## Fasson®

### INKJET PET MATT CLEAR S4700-HF100 FSC



INKJET PET MATT CLEAR

S4700

HF100 FSC



The mark of  
responsible forestry

*This is an automatically generated datasheet. All data to be considered as typical values and subject to change without prior notice. Further testing is always recommended.*

*If you would like to make a suggestion or comment on this datasheet, please send an email to [datasheet.mgmt@eu.averydennison.com](mailto:datasheet.mgmt@eu.averydennison.com)*

## Avery Dennison Materials Group Europe

Willem Einthovenstraat 11  
2342 BH Oegstgeest  
The Netherlands  
+31 (0)85 000 2000

### Warranty

All Avery Dennison statements, technical information and recommendations are based on tests believed to be reliable but do not constitute a guarantee or warranty. All Avery Dennison products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes. All Avery Dennison's products are sold subject to Avery Dennison's general terms and conditions of sale, see <http://terms.europe.averydennison.com>



©2026 Avery Dennison Corporation. All rights reserved. Avery Dennison and all other Avery Dennison brands, this publication, its content, product names and codes are owned by Avery Dennison Corporation. All other brands and product names are trademarks of their respective owners. This publication must not be used, copied or reproduced in whole or in part for any purposes other than marketing by Avery Dennison.