

Facestock

A matt, white, voided Polypropylene (PP) film with a clay-coating on both sides. Ideal for tag applications requiring high quality printing and medium strength.

Basis Weight	134 g/m²	ASTM D-3776
Caliper	180 µm	ISO 534
Elongation CD	<60 %	DIN 53455
Elongation MD	<150 %	DIN 53455
Opacity	95 %	DIN 53146
Whiteness	95+/-3 %	ISO 2470
Tensile strength MD	58 N/mm²	ASTM D-1922
Tensile strength CD	127 N/mm²	ASTM D-1922

Applications and Use

This product is ideal for applications such as wristbands on events or in hospitals, self-tie tags in garden centers and food identification labels. The product offers only limited tear propagation resistance.

Conversion and Printing

The product can be converted by all conventional roll conversion technologies including: Letterpress, Offset, Screenprinting, UV flexo and Water-based flexo. This product is also suitable for variable information printing in: Thermal Transfer printing systems. IMPORTANT NOTES: The absorbent coating provides a "paper like" surface to the film.

Shelf Life

To obtain optimal performance, use this product within one year of the date of manufacture, under storage conditions as defined by FINAT (20-25°C; 40-50%RH). Prolonged storage outside these conditions might reduce the shelf life.

Avery Dennison Materials Group Europe

Willem Einthovenstraat 11 2342 BH Oegstgeest The Netherlands +31 (0)85 000 2000


Warranty

All Avery Dennison statements, technical information and recommendations are based on tests believed to be reliable but do not constitute a guarantee or warranty. All Avery Dennison products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes. All Avery Dennison's products are sold subject to Avery Dennison's general terms and conditions of sale, see http://terms.europe.averydennison.com

AB512

Fasson ®

SYNTHETIC PAPER 2S-130



This is an automatically generated datasheet. All data to be considered as typical values and subject to change without prior notice. Further testing is always recommended.

If you would like to make a suggestion or comment on this datasheet, please send an email to datasheet.mgmt@eu.averydennison.com



©2023 Avery Dennison Corporation. All rights reserved. Avery Dennison and all other Avery Dennison brands, this publication, its content, product names and codes are owned by Avery Dennison Corporation. All other brands and product names are trademarks of their respective owners. This publication must not be used, copied or reproduced in whole or in part for any purposes other than marketing by Avery Dennison.