

### Facestock

A white high-gloss film with print receptive coating. Produced from wood pulp sourced from managed plantations. NatureFlex™ White and Clear film is certified OK compost INDUSTRIAL and OK compost HOME by our supplier (TÜV AUSTRIA, licensee number: S0020).

Basis Weight	65 g/m <sup>2</sup>	ISO 536
Caliper	45 µm	ISO 534

### Adhesive

A general purpose permanent, acrylic based adhesive.

### Liner

BG40WH FSC, a supercalandered siliconized white glassine paper.

The liner is made from FSC® certified paper (FSC Mix Credit, chain-of-custody number: CU-COC-807907, Licence Code: FSC-C004451).

Basis Weight	57 g/m <sup>2</sup>	ISO 536
Caliper	51 µm	ISO 534

### Laminate

Total Caliper	113 µm±10%	ISO 534
---------------	------------	---------

### Performance Data

Initial Tack	10 N/25mm	FTM 9 Glass
Peel Adhesion 90°	6 N/25mm	FTM 2 St.St.
Min. Application Temp.	5 °C	
Service Temperature	-20 °C to 80 °C	

### Adhesive Performance

S692N is a clear permanent adhesive featuring excellent UV resistance and weatherability together with good adhesion performance, even on apolar substrates.

### Applications and Use

It can be used for all kinds of applications, but is specifically suited for applications where the complete packaging should be biodegradable and where direct food contact is required. The NatureFlex film also has a good resistant to oils and grease. Natureflex is sensitive to temperature and humidity, these parameters will potentially cause the film to shrink. It's recommended to test suitability in the end user application under various conditions. It is also recommended the storage in its original wrapping away from any source of local heating or direct sunlight.


### Conversion and Printing

The product offers very good die-cutting properties. NatureFlex™ can be converted by flexographic and rotogravure printing processes. Nitrocellulose-based inks and water based inks are suitable. For applications on biodegradable packaging, the use of biodegradable inks is recommended. Please consult your printing ink supplier about suitable printing inks. Because of the heat sensitivity of the face stock the drying temperature needs to be reduced to the lowest possible temperature. Opposed to this, the air flow to dry the inks needs to be increased. With some ink systems, a low intensity Corona treatment and/or the use of a primer can improve the print quality.

## AD141

## Fasson®

### NATUREFLEX WHITE S692N-BG40WH FSC



NATUREFLEX WHITE

S692N

BG40WH FSC



The mark of  
responsible forestry

*This is an automatically generated datasheet. All data to be considered as typical values and subject to change without prior notice. Further testing is always recommended.*

*If you would like to make a suggestion or comment on this datasheet, please send an email to [datasheet.mgmt@eu.averydennison.com](mailto:datasheet.mgmt@eu.averydennison.com)*

### Compliance and Approvals

The adhesive S692N is suitable for contact with dry, moist and fatty foodstuffs with a reduction factor of 3 or higher in this construction. For complete information regarding the food contact compliance status, please contact your local sales representative for a Food Contact Statement.

### Shelf Life

To obtain optimal performance, use this product within half a year of the date of manufacture, under storage conditions as defined by FINAT (20-25°C; 40-50%RH). Prolonged storage outside these conditions might reduce the shelf life.

### Avery Dennison Materials Group Europe

Willem Einthovenstraat 11  
2342 BH Oegstgeest  
The Netherlands  
+31 (0)85 000 2000



### Warranty

All Avery Dennison statements, technical information and recommendations are based on tests believed to be reliable but do not constitute a guarantee or warranty. All Avery Dennison products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes. All Avery Dennison's products are sold subject to Avery Dennison's general terms and conditions of sale, see <http://terms.europe.averydennison.com>

©2025 Avery Dennison Corporation. All rights reserved. Avery Dennison and all other Avery Dennison brands, this publication, its content, product names and codes are owned by Avery Dennison Corporation. All other brands and product names are trademarks of their respective owners. This publication must not be used, copied or reproduced in whole or in part for any purposes other than marketing by Avery Dennison.