

# Facestock

A gloss, transparent, plain Polypropylene (PP) film with an acrylic TOP coating on both sides. Ideal for applications requiring high quality printing on the front side and adhesive laminating on the back side.

Basis Weight	83 g/m²	ISO 536
Caliper	92 µm	ISO 534
Gloss 45°	90 %	ASTM D 2457
Haze 2.5°	2.0 %	ASTM D 1003
Tensile strength MD	170 MN/m <sup>2</sup>	ASTM D 882
Tensile strength CD	160 MN/m <sup>2</sup>	ASTM D 882
Elongation ASTM MD	105 %	ASTM D 882
Elongation ASTM CD	120 %	ASTM D 882

## **Conversion and Printing**

This product has a top coating which gives outstanding printing performance across a wide variety of printing processes including flexography, letterpress, offset, silkscreen, gravure and hot or cold foiling processes. It is highly compatible with UV, water-based and solvent-based inks. However, exact ink and foil systems should be recommended by your ink supplier.

## Shelf Life

To obtain optimal performance, use this product within one year of the date of manufacture, under storage conditions as defined by FINAT (20-25°C; 40-50%RH). Prolonged storage outside these conditions might reduce the shelf life.

#### Avery Dennison Materials Group Europe Willem Einthovenstraat 11 2342 BH Oegstgeest The Netherlands +31 (0)85 000 2000


#### Warranty

All Avery Dennison statements, technical information and recommendations are based on tests believed to be reliable but do not constitute a guarantee or warranty. All Avery Dennison products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes. All Avery Dennison's products are sold subject to Avery Dennison's general terms and conditions of sale, see http://terms.europe.averydennison.com

# AD684

Fasson ®

# PP TOP CLEAR 2S-90



This is an automatically generated datasheet. All data to be considered as typical values and subject to change without prior notice. Further testing is always recommended.

If you would like to make a suggestion or comment on this datasheet, please send an email to datasheet.mgmt@eu.averydennison.com



©2025 Avery Dennison Corporation. All rights reserved. Avery Dennison and all other Avery Dennison brands, this publication, its content, product names and codes are owned by Avery Dennison Corporation. All other brands and product names are trademarks of their respective owners. This publication must not be used, copied or reproduced in whole or in part for any purposes other than marketing by Avery Dennison.