

Facestock

A White, uncoated matt 100% Cotton paper with a Unique 'Velvet finish' appearance. Wet strenght and fungicidal treatments.

Basis Weight 115 g/m 2 ISO 536 Caliper 217 μm ISO 534

Adhesive

A general purpose permanent, acrylic based adhesive.

Liner

BG45 white, a supercalendered glassine paper.

Laminate

Total Caliper 299 µm±10% ISO 534

Performance Data

Initial Tack 20 N/25mm FTM 9 Glass Peel Adhesion 90° 7 N/25mm FTM 2 St.St.

Min. Application Temp. 5 °C

Service Temperature -20 °C to 80 °C

Adhesive Performance

The adhesive features high initial tack, excellent adhesion and good low temperature performance on a wide variety of substrates. Specially designed for wine labelling applications it allows easy conversion of difficult label shapes.

Applications and Use

This product is designed for Wine labelling, it is suitable for primary labelling of high and premium goods eg: spirits, specialist foods. Due to its high stiffness it is not recommended for labelling on small diameter surfaces (eg. neck labels or mini bottles) or more difficult curved bottles. It is important to apply adequate pressure during the labelling process to ensure a good adhesion performance on the substrate. Care should be taken when adding embellishments as this will affect the adhesion. In addition bottles should be washed and dried before label application to ensure optimum adhesion. It is recommended to run a dispensing test in order to check that pressure is adequate, especially in case of more complex label shapes.

Conversion and Printing

Printable by Offset, Screen, Hot Foil. Due to the stiffness of the paper, the internal winding is not recommended.


Shelf Life

To obtain optimal performance, use this product within one year of the date of manufacture, under storage conditions as defined by FINAT (20-25°C; 40-50%RH). Prolonged storage outside these conditions might reduce the shelf life.

AD871

Fasson ®

COTTON WHITE S2030 INC-BG45WH



S2030
BG45WH

This is an automatically generated datasheet. All data to be considered as typical values and subject to change without prior notice. Further testing is always recommended.

If you would like to make a suggestion or comment on this datasheet, please send an email to datasheet.mgmt@eu.averydennison.com



Avery Dennison Materials Group Europe

Willem Einthovenstraat 11 2342 BH Oegstgeest The Netherlands +31 (0)85 000 2000

Warranty
All Avery Dennison statements, technical information and recommendations are based on tests believed to be reliable but do not constitute a guarantee or warranty. All Avery Dennison products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes. All Avery Dennison's products are sold subject to Avery Dennison's general terms and conditions of sale, see http://terms.europe.averydennison.com



©2024 Avery Dennison Corporation. All rights reserved. Avery Dennison and all other Avery Dennison brands, this publication, its content, product names and codes are owned by Avery Dennison Corporation. All other brands and product names are trademarks of their respective owners. This publication must not be used, copied or reproduced in whole or in part for any purposes other than marketing by Avery Dennison.