

### Facestock

A gloss, transparent, plain Polypropylene (PP) film with an acrylic TOP coating on one side. Ideal for wrap around label applications requiring high clarity and high quality printing.

Basis Weight	55 g/m <sup>2</sup>	ISO 536
Caliper	58 µm	ISO 534
Elasticity modulus MD	2900 MN/m <sup>2</sup>	DIN 53455
Elongation CD	110 %	DIN 53455
Elongation MD	80 %	DIN 53455
Gloss 45°	85 %	ASTM D 2457
Haze	<2 %	ASTM D1003
Tensile Str. MD	210 MN/m <sup>2</sup>	DIN 53455
Tensile Str. CD	170 MN/m <sup>2</sup>	DIN 53455

### Applications and Use

This product is ideal for applications such as wrap around labels on PET bottles, cut to size labels that are glued to the bottle with a hot-melt adhesive stripe on both edges and reinforcing of printed media.

### Conversion and Printing

The topcoated film can be printed by conventional and digital printing techniques such as UV flexo, UV Inkjet, screen, offset, letterpress, gravure, letterpress and hot or cold foiling processes. The topcoat is designed for optimal ink adhesion with UV-cured inks, including low migration inks, and is compatible with LED curing systems. The face material is suitable for Thermal Transfer printing. Exact inks, foils and ribbons should be specified by your ink/foil/ribbon supplier. On-press corona treatment is not advised. The material has very good register properties especially when a high number of different colors are used.

### Shelf Life

To obtain optimal performance, use this product within one year of the date of manufacture, under storage conditions as defined by FINAT (20-25°C; 40-50%RH). Prolonged storage outside these conditions might reduce the shelf life.

## AG117

## Fasson®

### PP TOP CLEAR 1S-60



PP TOP CLEAR 1S-60

*This is an automatically generated datasheet. All data to be considered as typical values and subject to change without prior notice. Further testing is always recommended.*

*If you would like to make a suggestion or comment on this datasheet, please send an email to [datasheet.mgmt@eu.averydennison.com](mailto:datasheet.mgmt@eu.averydennison.com)*

### Avery Dennison Materials Group Europe

Willem Einthovenstraat 11  
2342 BH Oegstgeest  
The Netherlands  
+31 (0)85 000 2000

#### Warranty

All Avery Dennison statements, technical information and recommendations are based on tests believed to be reliable but do not constitute a guarantee or warranty. All Avery Dennison products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes. All Avery Dennison's products are sold subject to Avery Dennison's general terms and conditions of sale, see <http://terms.europe.averydennison.com>



©2025 Avery Dennison Corporation. All rights reserved. Avery Dennison and all other Avery Dennison brands, this publication, its content, product names and codes are owned by Avery Dennison Corporation. All other brands and product names are trademarks of their respective owners. This publication must not be used, copied or reproduced in whole or in part for any purposes other than marketing by Avery Dennison.