

### Facestock

A gloss, transparent, uncoated, soft, highly plasticized PVC Cling film applied on a cast coated board liner. Ideal for labels that cling without adhesive on glossy surfaces, requiring easy removal of the label and without leaving any residue.

Basis Weight	319 g/m <sup>2</sup>	ISO 536
Caliper	298 µm	ISO 534
Min. Application Temp.	5 °C	
Caliper (film only)	150 µm	T411
Density	1.23 gr/cc	ASTM D792
Weight (liner only)	135 g/m <sup>2</sup>	ISO 536
Surface Tension	35 mN/m	measured with test inks
Service temp.	-20 to +70 °C	
Cling Adhesion	0.06 N/25mm	FTM1 on glass

### Applications and Use

Fasson Static Cling Clear PVC is a clear Vinyl that clings without adhesive on smooth, glossy surfaces like glass, PET, PMMA and PC. It could be easily removed and leaves no residues. However, we do recommend that in combination with laquers and plastics the compatibility has to be tested. The product could be reused / reapplied.

### Conversion and Printing

The product can be converted by conventional roll conversion technologies including: Screen, letterpress, UV flexo and UV Offset. **IMPORTANT NOTES:** - Due to the limited shelf life of this product we recommend to print the material immediately after delivery. The surface of the film may be marked by the back side of the release liner, due to time, temperature and roll length. For better gloss and transparency it is therefore recommended to use the material immediately. - The Expected Life Time of the printed label is up to 3 years in indoor conditions.

### Shelf Life

To obtain optimal performance, use this product within 60 days of the date of manufacture, under storage conditions as defined by FINAT (20-25°C; 40-50%RH). Prolonged storage outside these conditions might reduce the shelf life.

### Avery Dennison Materials Group Europe

Willem Einthovenstraat 11  
2342 BH Oegstgeest  
The Netherlands  
+31 (0)85 000 2000

### Warranty

All Avery Dennison statements, technical information and recommendations are based on tests believed to be reliable but do not constitute a guarantee or warranty. All Avery Dennison products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes. All Avery Dennison's products are sold subject to Avery Dennison's general terms and conditions of sale, see <http://terms.europeaverydennison.com>

## AG624

### Fasson ®

### STATIC CLING PVC CL-135



### STATIC CLING PVC CL-135

*This is an automatically generated datasheet. All data to be considered as typical values and subject to change without prior notice. Further testing is always recommended.*

*If you would like to make a suggestion or comment on this datasheet, please send an email to [datasheet.mgmt@eu.averydennison.com](mailto:datasheet.mgmt@eu.averydennison.com)*



©2026 Avery Dennison Corporation. All rights reserved. Avery Dennison and all other Avery Dennison brands, this publication, its content, product names and codes are owned by Avery Dennison Corporation. All other brands and product names are trademarks of their respective owners. This publication must not be used, copied or reproduced in whole or in part for any purposes other than marketing by Avery Dennison.