

Facestock

A white polyester-faced laminated pouching material used in packaging of snack foods. Adhesive coated two layer laminate (PET 12μ SiOx/PE white 50μ).

$(PET 12\mu 3IOX/PE WITHE 30\mu)$.		
Basis Weight	72.6 g/m ²	ISO 536
Caliper	62 µm	ISO 534
Elongation at break CD	>60 %	DIN 53455
Elongation at break MD	>60 %	DIN 53455
Oxygen Permeability (23°C;	0,4 -	ASTM D3985
50%RH)	0,6 cm ³ /m ² /24	
	hr	
2% Secant Modulus MD	>850 N/mm ²	DIN EN ISO
2% Secant Modulus MD	>900 N/mm²	527 T 3 DIN EN ISO
2 /6 Secant Modulus MD	2900 N/IIIII	527 T 3
Flexural Modulus Fmax MD	>250 mN	SCAN P
		29/DIN 52 121
Flexural Modulus Fmax CD	>300 mN	SCAN P
		29/DIN 52 121
Tear Elmendorf MD	>0.25 N	DIN EN 21974
Tear Elmendorf CD	>0.35 N	DIN EN 21974
Tensile Stren. MD	>50 N/mm ²	ISO 527-3
Tensile Stren. CD	>45 N/mm ²	ISO 527-3
Water Vapor Transmission	0,1 -	ASTM F1249
Rate (38°C; 90% RH)	0,2 g/m ² /24 hr	
Sealing Strength	>30 N/15mm	DIN 52
		529@140°C/5
		bar/0.5sec
Coefficient of Friction	0,15 - 0,30 µs	ASTM D1895
Inside/Inside	0.00 0.50	A OTAL D4005
Coefficient of Friction	0,30 - 0,50 µs	ASTM D1895
Outside/Outside		

Applications and Use

Heatsealable Flexible packaging laminates for nuts and other oxygen sensitive salted snacks or general-purpose snack good applications. White PET with Nano coating providing reduced OTR.

Conversion and Printing


The white corona treated PET face provides printability via Flexo. Shelf Life

To obtain optimal performance, use this product within half a year of the date of manufacture, under storage conditions as defined by FINAT (20-25°C; 40-50%RH). Prolonged storage outside these conditions might reduce the shelf life.

AO602

Fasson ®

SNACK WEB WHITE62 NANO



SNACK WEB WHITE62 NANO

This is an automatically generated datasheet. All data to be considered as typical values and subject to change without prior notice. Further testing is always recommended.

If you would like to make a suggestion or comment on this datasheet, please send an email to datasheet.mgmt@eu.averydennison.com



Avery Dennison Materials Group Europe

Willem Einthovenstraat 11 2342 BH Oegstgeest The Netherlands +31 (0)85 000 2000

Warranty
All Avery Dennison statements, technical information and recommendations are based on tests believed to be reliable but do not constitute a guarantee or warranty. All Avery Dennison products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes. All Avery Dennison's products are sold subject to Avery Dennison's general terms and conditions of sale, see http://terms.europe.averydennison.com



©2023 Avery Dennison Corporation. All rights reserved. Avery Dennison and all other Avery Dennison brands, this publication, its content, product names and codes are owned by Avery Dennison Corporation. All other brands and product names are trademarks of their respective owners. This publication must not be used, copied or reproduced in whole or in part for any purposes other than marketing by Avery Dennison.