

# Facestock

A gloss, transparent, uncoated shrink PET film. Ideal for shrink sleeve applications requiring top to bottom container decoration and up to 75% transversal shrinkage (in CD).

Basis Weight	58.5 g/m²	ISO 536
Caliper	45 µm	ISO 4593
Elongation CD	40 %	ISO 527
Elongation MD	400 %	ISO 527
Tensile strength MD	50 MPa	ISO 527
Tensile strength CD	250 MPa	ISO 527
Shrinkage MD	<=3 %	95°C
Shrinkage CD	77+/-2 %	30 sec. in
		water

## Applications and Use

This product is ideal for applications such as sleeves for dairy products in round shaped bottles, promotional beer bottle sleeves for football events and eye-catching sleeves for sparkling wine bottles.

## **Conversion and Printing**

The product can be converted by the following conventional roll conversion technologies: flexo, offset and rotogravure. Compatible with solvent and UV inks. IMPORTANT NOTS: Exact ink systems should be recommended by your ink supplier and special care should be taken regarding web temperature and winding tension.

#### Shelf Life

To obtain optimal performance, use this product within one year of the date of manufacture, under storage conditions as defined by FINAT (20-25°C; 40-50%RH). Prolonged storage outside these conditions might reduce the shelf life.


Avery Dennison Materials Group Europe Willem Einthovenstraat 11 2342 BH Oegstgeest The Netherlands +31 (0)85 000 2000

#### Warranty

All Avery Dennison statements, technical information and recommendations are based on tests believed to be reliable but do not constitute a guarantee or warranty. All Avery Dennison products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes. All Avery Dennison's products are sold subject to Avery Dennison's general terms and conditions of sale, see http://terms.europe.averydennison.com

# AQ912

Fasson ® SHRINK PET CL 1S-45 UHS



# SHRINK PET CL 1S-45 UHS

This is an automatically generated datasheet. All data to be considered as typical values and subject to change without prior notice. Further testing is always recommended.

If you would like to make a suggestion or comment on this datasheet, please send an email to datasheet.mgmt@eu.averydennison.com



©2022 Avery Dennison Corporation. All rights reserved. Avery Dennison and all other Avery Dennison brands, this publication, its content, product names and codes are owned by Avery Dennison Corporation. All other brands and product names are trademarks of their respective owners. This publication must not be used, copied or reproduced in whole or in part for any purposes other than marketing by Avery Dennison.