

### Facestock

Acetate Satin Cloth is a white acetate satin fabric with high opacity and lustrous finish.

Basis Weight	125 g/m <sup>2</sup>	ISO 536
Caliper	160 µm	ISO 534

### Adhesive

A general purpose permanent, acrylic based adhesive.

### Liner

BG50 white, a supercalendered glassine paper.

The liner is made from FSC® certified paper (FSC Mix Credit, chain-of-custody number: CU-COC-807907, Licence Code: FSC-C004451).

Basis Weight	79 g/m <sup>2</sup>	ISO 536
Caliper	69 µm	ISO 534

### Laminate

Total Caliper	252 µm±10%	ISO 534
---------------	------------	---------

### Performance Data

Initial Tack	12 N/25mm	FTM 9 Glass
Peel Adhesion 90°	8 N/25mm	FTM 2 St.St.
Min. Application Temp.	5 °C	
Service Temperature	-20 °C to 80 °C	

### Adhesive Performance

S692N is a clear permanent adhesive featuring excellent UV resistance and weatherability together with good adhesion performance, even on apolar substrates.

### Applications and Use

Acetate Satin Cloth material is mainly used in attractive quality labels including conference badges, promotional stickers etc and *Suitable for mattresses, textiles, shoes and carpets based on adhesive selection.*

### Conversion and Printing

Acetate Satin Cloth has very good printing properties for letterpress, flexo and offset processing. Apply a thin ink coating only. For letterpress use the lowest possible pressure. For screen printing a fine screen mesh is recommended.

### Compliance and Approvals

The adhesive S692N is suitable for contact with dry, moist and fatty foodstuffs with a reduction factor of 3 or higher in this construction. For complete information regarding the food contact compliance status, please contact your local sales representative for a Food Contact Statement.

### Shelf Life

To obtain optimal performance, use this product within two years of the date of manufacture, under storage conditions as defined by FINAT (20-25°C; 40-50%RH). Prolonged storage outside these conditions might reduce the shelf life.

## AR708

## Fasson®

### ACETATE SATINCLOTH WHITE S692N-BG50WH FSC



ACETATE SATINCLOTH WHITE	
-----------------------------	--

S692N	
-------	---

BG50WH FSC	
------------	---



The mark of  
responsible forestry

*This is an automatically generated datasheet. All data to be considered as typical values and subject to change without prior notice. Further testing is always recommended.*

*If you would like to make a suggestion or comment on this datasheet, please send an email to [datasheet.mgmt@eu.averydennison.com](mailto:datasheet.mgmt@eu.averydennison.com)*

## Avery Dennison Materials Group Europe

Willem Einthovenstraat 11  
2342 BH Oegstgeest  
The Netherlands  
+31 (0)85 000 2000



### Warranty

All Avery Dennison statements, technical information and recommendations are based on tests believed to be reliable but do not constitute a guarantee or warranty. All Avery Dennison products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes. All Avery Dennison's products are sold subject to Avery Dennison's general terms and conditions of sale, see <http://terms.europe.averydennison.com>

©2026 Avery Dennison Corporation. All rights reserved. Avery Dennison and all other Avery Dennison brands, this publication, its content, product names and codes are owned by Avery Dennison Corporation. All other brands and product names are trademarks of their respective owners. This publication must not be used, copied or reproduced in whole or in part for any purposes other than marketing by Avery Dennison.