

Facestock

A white high-gloss film with print receptive coating. Produced from wood pulp sourced from managed plantations. The NatureFlex[™] film complies to the EN 13432 standard for composting and is OK Compost Industrial and OK Comost Home certifed (the self-adheisve laminate does not have certification for composting).

Basis Weight	64.5 g/m²	ISO 536
Caliper	42 µm	ISO 534

Adhesive

C3 is a transparent, dispersion-based removable, acrylic adhesive.

Liner

BG40WH FSC, a supercalandered siliconized white glassine paper.

The liner is made from FSC® certified paper (FSC Mix Credit, chain-of-custody number: CU-COC-807907, Licence Code: FSC-C004451).

Basis Weight	57 g/m²	ISO 536
Caliper	51 µm	ISO 534
Laminate		
Total Caliper	113 µm±10%	ISO 534
Performance Data		
Initial Tack	4 N/25mm	FTM 9 Glass
Peel Adhesion 90°	2.5 N/25mm	FTM 2 St.St.
Min. Application Temp.	0 °C	
Service Temperature	-40 °C to 100	
	°C	

Adhesive Performance

C3 is a highly transparent adhesive with high ageing stability for removable labels, e.g. for cosmetics and pharmacy applications.

Applications and Use

It can be used for all kinds of applications, but is specifically suited for applications where the complete packaging should be biodegradable and where direct food contact is required. The NatureFlex film also has a good resistant to oils and grease.

Because of its nature (cellulose based) care should taken in wet conditions for long terms applications, preliminary tests are therefore recommended prior to use.

C3 removes clean from many substrates from polymeric (PET, PP, ABS, PS), fiberboard, aluminium, stainless steel, glass, window labelling (with limited outdoor UV exposure). Preliminary testing is recommended.


Conversion and Printing

The product offers very good die-cutting properties. NatureFlex™ can be converted by flexographic and rotogravure printing processes. Nitrocellulose-based inks and water based inks are suitable. For applications on biodegradable packaging, the use of biodegradable inks is recommended. Please consult your printing ink supplier about suitable printing inks.

AV740

Fasson ®

NATUREFLEX TOP WHITE C3-BG40WH FSC



NATUREFLEX TOP WH 1S-45

C3

BG40WH FSC



This is an automatically generated datasheet. All data to be considered as typical values and subject to change without prior notice. Further testing is always recommended.

If you would like to make a suggestion or comment on this datasheet, please send an email to datasheet.mgmt@eu.averydennison.com



Because of the heat sensitivity of the face stock the drying temperature needs to be reduced to the lowest possible temperature. Opposed to this, the air flow to dry the inks needs to be increased.

Compliance and Approvals

The adhesive C3 is suitable for contact with dry, moist, and nonfatty foodstuffs in this construction. For complete information regarding the food contact compliance status, please contact your local sales representative for a Food Contact Statement.

Shelf Life

To obtain optimal performance, use this product within half a year of the date of manufacture, under storage conditions as defined by FINAT (20-25°C; 40-50%RH). Prolonged storage outside these conditions might reduce the shelf life.

Avery Dennison Materials Group Europe

Willem Einthovenstraat 11 2342 BH Oegstgeest The Netherlands +31 (0)85 000 2000



Warranty

All Avery Dennison statements, technical information and recommendations are based on tests believed to be reliable but do not constitute a guarantee or warranty. All Avery Dennison products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes. All Avery Dennison's products are sold subject to Avery Dennison's general terms and conditions of sale, see <u>http://terms.europe.averydennison.com</u> ©2025 Avery Dennison Corporation. All rights reserved. Avery Dennison and all other Avery Dennison brands, this publication, its content, product names and codes are owned by Avery Dennison Corporation. All other brands and product names are trademarks of their respective owners. This publication must not be used, copied or reproduced in whole or in part for any purposes other than marketing by Avery Dennison.