

Facestock

A semi-gloss, white, triple-layer adhesive coated PP laminate with a thermal transfer printable paper on both sides. Ideal for commercial tagging applications requiring high quality printing and good tear resistance. The paper has 30% recycled content.

Basis Weight	197 g/m ²	ISO 536
Caliper	172 µm	ISO 534
Caliper (film only)	40 µm	T411
Weight (base paper)	80 g/m ²	ISO 536

Applications and Use

Typical applications are name tags on luggages. This product is also used for multi-use tickets or garment hang tags. Its multi-layer structure gives this product a very high resistance against tearing combined with the possibility to print variable information in an easy to use thermal VI printers.

Conversion and Printing

This Thermal Transfer face material is suitable for solid and halftone images and text printing by letterpress, flexo (UV and waterbased) offset and screen processes. Hot and cold foil stamping, varnishing and variable imprinting with thermal transfer are also suitable for this product.

Being produced from 30% post consumer waste paper, there is a possible higher incidence of impurities in the product compared to virgin fiber products.

Shelf Life

To obtain optimal performance, use this product within one year of the date of manufacture, under storage conditions as defined by FINAT (20-25°C; 40-50%RH). Prolonged storage outside these conditions might reduce the shelf life.

Avery Dennison Materials Group Europe

Willem Einthovenstraat 11
2342 BH Oegstgeest
The Netherlands
+31 (0)85 000 2000

Warranty

All Avery Dennison statements, technical information and recommendations are based on tests believed to be reliable but do not constitute a guarantee or warranty. All Avery Dennison products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes. All Avery Dennison's products are sold subject to Avery Dennison's general terms and conditions of sale, see <http://terms.europe.averydennison.com>

BB305

Fasson ®

TRITAG TT rMC CARD185 PP



TRITAG TT RMC CARD185
PP

This is an automatically generated datasheet. All data to be considered as typical values and subject to change without prior notice. Further testing is always recommended.

If you would like to make a suggestion or comment on this datasheet, please send an email to datasheet.mgmt@eu.averydennison.com



©2025 Avery Dennison Corporation. All rights reserved. Avery Dennison and all other Avery Dennison brands, this publication, its content, product names and codes are owned by Avery Dennison Corporation. All other brands and product names are trademarks of their respective owners. This publication must not be used, copied or reproduced in whole or in part for any purposes other than marketing by Avery Dennison.