

Facestock

A matt, white, triple-layer adhesive coated PET laminate with a direct thermal printable paper on one side. Ideal for stapeled Tag's on wooden boxes requiring good resistance to moisture and contaminants and high tear resistance.

Basis Weight 230 g/m² **ISO 536 ISO 534** Caliper 193 µm Caliper (film only) 50 µm T411 Weight (base paper) **ISO 536** 80 g/m²

Applications and Use

This product is ideal for applications such as stapeled Tag's on wooden boxes or pallets, heavy duty tags like poastal bag tags and commercial tags.

Conversion and Printing

The product can be converted by all conventional roll conversion technologies including: Letterpress, Offset, Screenprinting, UV flexo and Water-based flexo. This product is also suitable for variable information printing in: Direct thermal printing systems at printing speeds up to 200 mm/sec (based on the printer's set up). IMPORTANT NOTES: Due to the thermographic properties, exposure above 50°C may cause premature imaging or discolouration. Inks containing alcohol or volatile organic solvents may cause discolouration of the thermosensitive coating. It is advisable to test inks and varnishes before conversion.

Shelf Life

To obtain optimal performance, use this product within one year of the date of manufacture, under storage conditions as defined by FINAT (20-25°C; 40-50%RH). Prolonged storage outside these conditions might reduce the shelf life.

Avery Dennison Materials Group Europe

Willem Einthovenstraat 11 2342 BH Oegstgeest The Netherlands +31 (0)85 000 2000

Warranty

All Avery Dennison statements, technical information and recommendations are based on tests believed to be reliable but do not constitute a guarantee or warranty. All Avery Dennison products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes. All Avery Dennison's products are sold subject to Avery Dennison's general terms and conditions of sale, see http://terms.europe.averydennison.com

BE145

Fasson ®

TRITAG TH-T CARD 230 PET



This is an automatically generated datasheet. All data to be considered as typical values and subject to change without prior notice. Further testing is always recommended.

If you would like to make a suggestion or comment on this datasheet, please send an email to datasheet.mgmt@eu.averydennison.com



©2023 Avery Dennison Corporation, All rights reserved, Avery Dennison and all other Avery Dennison brands, this publication, its content, product names and codes are owned by Avery Dennison Corporation. All other brands and product names are trademarks of their respective owners. This publication must not be used, copied or reproduced in whole or in part for any purposes other than marketing by Avery Dennison.