

Facestock

White, machine coated, semi-gloss appearance with 30% recycled content.

The facestock is made from FSC® certified paper (FSC Mix Credit, chain-of-custody number: CU-COC-807907, Licence Code: FSC-C004451)

Basis Weight	78 g/m ²	ISO 536
Caliper	64 µm	ISO 534

Adhesive

A Permanent, acrylic based adhesive

Liner

HF120, a one side coated, bleached kraft paper.

Basis Weight	121 g/m ²	ISO 536
Caliper	118 µm	ISO 534

Laminate

Total Caliper	192 µm±10%	ISO 534
---------------	------------	---------

Performance Data

Initial Tack	5 N/25mm	FTM 9 Glass
Peel Adhesion 90°	3.5 N/25mm	FTM 2 St.St.
Min. Application Temp.	10 °C	
Service Temperature	-20 °C to 80 °C	

Adhesive Performance

The adhesive S5200N has been developed with a high cohesive strength and 'hard' low migratory nature. This combination prevents deep penetration into fibres and subsequent adhesive transfer, staining, fibre pick or disruption. The adhesive gives a balanced level of adhesion versus clean removability on a wide variety of natural and man made textile types and finishes i.e. cotton, lambs wool, cotton and cotton/acrylic blends. NB. Application of any self adhesive material onto particularly sensitive surfaces such as silk, suede and leathers should be undertaken with caution. While S5200N has proven to give clean removability from a wide range of fibres pre-testing with all fabric types to be labelled is still recommended.

Applications and Use

30% post consumer waste recycled material suitable as a general labelling material with very good sustainability credentials. A solution for logistics applications, warehousing or inventory labels on cardboard and paper substrates.

The product is a result of the increasing need by retailers to provide additional 'temporary' customer information on garments. Typical applications are in-store 'size labelling' of both folded and hanging clothing to provide the consumer with a easy visual method of selecting the correct size – and the retailer with reduced disruption of garments whilst on display. 'Temporary' self adhesive labels are also used for in-store promotion and branding, to highlight fibre combination or trade marked fibres – and in 'tracking' throughout the garment manufacturing process itself.

The hygroflat backing paper is specially suited to the more critical refolding demands of high-speed computer printers, providing optimum layflatness and excellent interfolding characteristics.

BE216

Fasson®

rMC PRIMECOAT FSC S5200N-HF120



RMC PRIMECOAT FSC

S5200N

HF120



The mark of responsible forestry

This is an automatically generated datasheet. All data to be considered as typical values and subject to change without prior notice. Further testing is always recommended.

If you would like to make a suggestion or comment on this datasheet, please send an email to datasheet.mgmt@eu.averydennison.com

Conversion and Printing

Suitable for solid and halftone images and text printing by letterpress, flexo (UV and waterbased) offset and screen processes. Hot and cold foil stamping, varnishing and variable imprinting with thermal transfer are also suitable for this product. Being produced from 30% post consumer waste paper, there is a possible higher incidence of impurities in the product compared to virgin fiber products.

Shelf Life

To obtain optimal performance, use this product within two years of the date of manufacture, under storage conditions as defined by FINAT (20-25°C; 40-50%RH). Prolonged storage outside these conditions might reduce the shelf life.

Avery Dennison Materials Group Europe

Willem Einthovenstraat 11
2342 BH Oegstgeest
The Netherlands
+31 (0)85 000 2000

Warranty

All Avery Dennison statements, technical information and recommendations are based on tests believed to be reliable but do not constitute a guarantee or warranty. All Avery Dennison products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes. All Avery Dennison's products are sold subject to Avery Dennison's general terms and conditions of sale, see <http://terms.europe.averydennison.com>



©2026 Avery Dennison Corporation. All rights reserved. Avery Dennison and all other Avery Dennison brands, this publication, its content, product names and codes are owned by Avery Dennison Corporation. All other brands and product names are trademarks of their respective owners. This publication must not be used, copied or reproduced in whole or in part for any purposes other than marketing by Avery Dennison.