

### Facestock

A white matt, uncoated, smooth woodfree printing paper. Wet strength, fungicidal treatments and very good wet opacity. The rPLUS underlamine contains 70% post consumer recycled content (PCR), ensuring optimum performances in the ice bucket, and in wet conditions in general, by minimizing the risk of wrinkling of the material.

The facestock is made from FSC® certified paper (FSC Mix Credit, chain-of-custody number: CU-COC-807907, Licence Code: FSC-C004451)

Basis Weight	215 g/m <sup>2</sup>	ISO 536
Caliper	211 µm	ISO 534

### Laminate

Total Caliper	211 µm±10%	ISO 534
---------------	------------	---------

### Applications and Use

This product is designed for Wine labelling, it is suitable for primary labelling of high and premium goods e.g. spirits, specialist foods. Due to its high stiffness it is not recommended for labelling on small diameters, neck labels in particular.

### Conversion and Printing

Printable by all conventional printing techniques. Due to open and textured nature of the facematerial, best results are in general from those techniques with maximum conformability of printing plate such as flexo and offset. Excellent results, in line with desired image, using offset or screen.

### Compliance and Approvals

The laminate is made with FSC® certified paper (FSC Mix Credit, chain-of-custody number: CU-COC-807907, Licence Code: FSC-C004451)


### Shelf Life

To obtain optimal performance, use this product within two years of the date of manufacture, under storage conditions as defined by FINAT (20-25°C; 40-50%RH). Prolonged storage outside these conditions might reduce the shelf life.

## BE969

## Fasson ®

### SABLE BLANC rPLUS FSC S2047N-BG45WH FSC



SABLE BLANC RPLUS FSC



*This is an automatically generated datasheet. All data to be considered as typical values and subject to change without prior notice. Further testing is always recommended.*

*If you would like to make a suggestion or comment on this datasheet, please send an email to [datasheet.mgmt@eu.averydennison.com](mailto:datasheet.mgmt@eu.averydennison.com)*

### Avery Dennison Materials Group Europe

Willem Einthovenstraat 11  
2342 BH Oegstgeest  
The Netherlands  
+31 (0)85 000 2000

### Warranty

All Avery Dennison statements, technical information and recommendations are based on tests believed to be reliable but do not constitute a guarantee or warranty. All Avery Dennison products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes. All Avery Dennison's products are sold subject to Avery Dennison's general terms and conditions of sale, see <http://terms.europe.averydennison.com>



©2024 Avery Dennison Corporation. All rights reserved. Avery Dennison and all other Avery Dennison brands, this publication, its content, product names and codes are owned by Avery Dennison Corporation. All other brands and product names are trademarks of their respective owners. This publication must not be used, copied or reproduced in whole or in part for any purposes other than marketing by Avery Dennison.