

Facestock

A polypropylene film with a matt white topcoat.

Basis Weight	47 g/m ²	ISO 536
Caliper	70 µm	ISO 534

Adhesive

C3 is a transparent, dispersion-based removable, acrylic adhesive.

Liner

BG40WH FSC, a supercalandered siliconized white glassine paper.

The liner is made from FSC® certified paper (FSC Mix Credit, chain-of-custody number: CU-COC-807907, Licence Code: FSC-C004451).

Basis Weight	57 g/m ²	ISO 536
Caliper	51 µm	ISO 534

Laminate

Total Caliper	138 µm±10%	ISO 534
---------------	------------	---------

Performance Data

Initial Tack	4 N/25mm	FTM 9 Glass
Peel Adhesion 90°	2.5 N/25mm	FTM 2 St.St.
Min. Application Temp.	0 °C	
Service Temperature	-40 °C to 100 °C	

Adhesive Performance

C3 is a highly transparent adhesive with high ageing stability for removable labels, e.g. for cosmetics and pharmacy applications.

Applications and Use

Very good candidate for a wide range of printing and finishing applications where durability, strength, moisture, grease and chemical resistance are required.

C3 removes clean from many substrates from polymeric (PET, PP, ABS, PS), fiberboard, aluminium, stainless steel, glass, window labelling (with limited outdoor UV exposure). Preliminary testing is recommended.

Conversion and Printing

The matt top coating can be printed by most conventional printing technologies (offset, letterpress, flexo and screen) and also suitable for Thermal Transfer printing. Printing inks and ribbons should be tested and qualified prior to use.

Compliance and Approvals

The adhesive C3 is suitable for contact with dry, moist, and non-fatty foodstuffs in this construction. For complete information regarding the food contact compliance status, please contact your local sales representative for a Food Contact Statement.

Shelf Life

To obtain optimal performance, use this product within two years of the date of manufacture, under storage conditions as defined by FINAT (20-25°C; 40-50%RH). Prolonged storage outside these conditions might reduce the shelf life.

BM131

Fasson®

TRANSFER PP70 MATT WH C3-BG40WH FSC



TRANSFER PP70 MATT
WHITE

C3

BG40WH FSC



The mark of
responsible forestry

This is an automatically generated datasheet. All data to be considered as typical values and subject to change without prior notice. Further testing is always recommended.

If you would like to make a suggestion or comment on this datasheet, please send an email to datasheet.mgmt@eu.averydennison.com

Avery Dennison Materials Group Europe

Willem Einthovenstraat 11
2342 BH Oegstgeest
The Netherlands
+31 (0)85 000 2000



Warranty

All Avery Dennison statements, technical information and recommendations are based on tests believed to be reliable but do not constitute a guarantee or warranty. All Avery Dennison products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes. All Avery Dennison's products are sold subject to Avery Dennison's general terms and conditions of sale, see <http://terms.europe.averydennison.com>

©2025 Avery Dennison Corporation. All rights reserved. Avery Dennison and all other Avery Dennison brands, this publication, its content, product names and codes are owned by Avery Dennison Corporation. All other brands and product names are trademarks of their respective owners. This publication must not be used, copied or reproduced in whole or in part for any purposes other than marketing by Avery Dennison.