

Facestock

An extra white, co-extruded and cavitated PP laminated on a TOP protected direct thermal paper, tear-resistant, used in food applications for fruit bag tags.

The facestock is made from FSC® certified paper (FSC Mix Credit, chain-of-custody number: CU-COC-807907, Licence Code: FSC-C004451)

Basis Weight	180 g/m ²	ISO 536
Caliper	232 µm	ISO 534
Weight (base paper)	110 g/m ²	ISO 536
Caliper Face	110 my	ISO 534
Caliper backing	120 my	ISO 534

Applications and Use

This expanded polypropylene laminate is generally used as tags in the fruit distribution. The product can be stapled onto a net of fruit. The foamed PP gives the product a soft touch, a certain water resistance and a very high CD tear resistance. This product was developed for applications where extra high breaking strength is required.

Conversion and Printing

The expanded polypropylene side can be printed with flexo and screen printing. The direct thermal paper side can be printed with the standard printing methods like letterpress, flexo, offset, gravure and of course direct thermal printing. Exact inks should be specified by your ink supplier. Especially with UV based flexo inks care should be taken in selection and preliminary testing is recommended.

IMPORTANT NOTE

This material has an inherent curl in both machine and cross directions. We measure this curl against our internal specifications to ensure it falls within acceptable tolerances before delivery. These tolerances are derived from empirical data.

Shelf Life

To obtain optimal performance, use this product within one year of the date of manufacture, under storage conditions as defined by FINAT (20-25°C; 40-50%RH). Prolonged storage outside these conditions might reduce the shelf life.

BO398

Fasson ®

FRUITAG TOP240 WH NG FSC



FRUITAG TOP240 WH NG
FSC



The mark of
responsible forestry

This is an automatically generated datasheet. All data to be considered as typical values and subject to change without prior notice. Further testing is always recommended.

If you would like to make a suggestion or comment on this datasheet, please send an email to datasheet.mgmt@eu.averydennison.com

Avery Dennison Materials Group Europe

Willem Einthovenstraat 11
2342 BH Oegstgeest
The Netherlands
+31 (0)85 000 2000

Warranty

All Avery Dennison statements, technical information and recommendations are based on tests believed to be reliable but do not constitute a guarantee or warranty. All Avery Dennison products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes. All Avery Dennison's products are sold subject to Avery Dennison's general terms and conditions of sale, see <http://terms.europe.averydennison.com>



©2025 Avery Dennison Corporation. All rights reserved. Avery Dennison and all other Avery Dennison brands, this publication, its content, product names and codes are owned by Avery Dennison Corporation. All other brands and product names are trademarks of their respective owners. This publication must not be used, copied or reproduced in whole or in part for any purposes other than marketing by Avery Dennison.