

Facestock

White, machine coated, semi-gloss appearance with 30% recycled content.

The facestock is made from FSC® certified paper (FSC Mix Credit, chain-of-custody number: CU-COC-807907, Licence Code: FSC-C004451)

Basis Weight 78 g/m^2 ISO 536 Caliper $64 \text{ } \mu \text{m}$ ISO 534

Adhesive

R5050 is an emulsion acrylic based removable adhesive.

Liner

BG40 BROWN FSC certified, supercalendered glassine paper. The liner is made from FSC® certified paper (FSC Mix Credit, chain-of-custody number: CU-COC-807907, Licence Code: FSC-C004451).

Basis Weight 54 g/m^2 ISO 536 Caliper $47 \mu \text{m}$ ISO 534

Laminate

Total Caliper 127 µm±10% ISO 534

Performance Data

Initial Tack 5 N/25mm FTM 9 Glass Peel Adhesion 90° 3 N/25mm FTM 2 St.St.

Min. Application Temp. 5 °C

Service Temperature -25 °C to 70 °C

Adhesive Performance

The adhesive features good tack and adhesion in combination with superior and clean removability from most substrates. The adhesive allows label application at a wide temperature range, and it retains its removable properties even at very low temperatures.

Applications and Use

30% post consumer waste recycled material suitable as a general labelling material with very good sustainabilty credentials.

Promotional labels / stickers, with good removability from most substrates. The product is also suitable for general deep freeze applications. In addition to an excellent general application performance on a wide range of primary and secondary food packaging the product can be used successfully in applications involving direct labeling of moist and fatty foodstuffs.


Conversion and Printing

Suitable for solid and halftone images and text printing by letterpress, flexo (UV and waterbased) offset and screen processes. Hot and cold foil stamping, varnishing and variable imprinting with thermal transfer are also suitable for this product. Being produced from 30% post consumer waste paper, there is a possible higher incidence of impurities in the product compared to virgin fiber products.

BQ263

Fasson ®

rMC PRIMECOAT FSC R5050-BG40BR FSC



RMC PRIMECOAT FSC

R5050

BG40BR FSC



The mark of responsible forestry

This is an automatically generated datasheet. All data to be considered as typical values and subject to change without prior notice. Further testing is always recommended.

If you would like to make a suggestion or comment on this datasheet, please send an email to datasheet.mgmt@eu.averydennison.com



Compliance and Approvals

The adhesive R5050 is suitable for contact with dry, moist, and fatty foodstuffs that have a reduction factor of 3 or higher in this construction. For complete information regarding the food contact compliance status, please contact your local sales representative for a Food Contact Statement.

The laminate is made with FSC® certified paper (FSC Mix Credit, chain-of-custody number: CU-COC-807907, Licence Code: FSC-C004451)

Shelf Life

To obtain optimal performance, use this product within two years of the date of manufacture, under storage conditions as defined by FINAT (20-25°C; 40-50%RH). Prolonged storage outside these conditions might reduce the shelf life.

Avery Dennison Materials Group Europe

Willem Einthovenstraat 11 2342 BH Oegstgeest The Netherlands +31 (0)85 000 2000



All Avery Dennison statements, technical information and recommendations are based on tests believed to be reliable but do not constitute a guarantee or warranty. All Avery Dennison products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes. All Avery Dennison's products are sold subject to Avery Dennison's general terms and conditions of sale, see http://terms.europe.averydennison.com



©2025 Avery Dennison Corporation. All rights reserved. Avery Dennison and all other Avery Dennison brands, this publication, its content, product names and codes are owned by Avery Dennison Corporation. All other brands and product names are trademarks of their respective owners. This publication must not be used, copied or reproduced in whole or in part for any purposes other than marketing by Avery Dennison.